

Classic Organ Works

2800 John Street, Unit 4, Markham, Ontario CANADA L3R 0E2
www.organworks.com 905-475-1275 or 1-888-812-9717 info@organworks.com

CTRL-3: Control Panel



Description

The Classic Organ Works Control Panel type CTRL-3 contains up to 10 momentary-action lighted push-buttons that are used for the main control functions of the organ.

The push-buttons are relegendable as required using laser-printed film.

Above the push-buttons is a vacuum-fluorescent display with four lines of twenty characters. This shows the current state of the control system but is also used for diagnostics and to detail the setting-up procedures for the many optional features of the organ.

The unit is intended to mount through a 3/4" wooden panel. A bezel can be supplied and the ribbon cable for the display is provided. The display can be supplied without the push-buttons if necessary (VFD-1).

Applications

To control Classic OrganWorks organ consoles and show the state of the organ during normal playing (Crescendo position, Transposer, Memory Level, etc.) or while using the built-in sequencer. It also indicates the state of control functions during setup while giving setting-up instructions to avoid referring to the written manual.

Features

- Compatible with both matrixed piston wiring directly to a CCC, or with parallel wiring to a CCU (packaged system).
- Basic format is ten pushbuttons (CTRL-3/10), but a partly-loaded version with only six push-buttons in three vertical pairs is also available (CTRL-3/6).
- Push-buttons may be used for any control function required by the Console Control Computer.
- Large, lighted, re-legendable, 3/4"-square EAO push-buttons.
- Isolated power input (either polarity) via terminal block or co-axial power jack (from an adaptor).
- Power for display can be from the normal unregulated chamber supply (+10V d.c. to +18V d.c.), or from the console computer.
- Panel protected by resettable fuses.
- Lamps can be powered by panel supply or console computer (normal).
- Lamps are 12-14V bi-pin type and are replaceable by removing the switch cap.
- No special cooling necessary.
- Dimensions: 4.5" x 4.125" x 1.9" (W x H x D (from the push-button tops)).